

GF Piping Systems Datasheet

valid from
5/30/12

MSA 330

MSA 330 Electrofusion unit with jointing data recording



The MSA 330 electrofusion unit combines high performance in jointing with easy and safe handling. The internal memory has a capacity of 500 jointing records, for data transfer the unit is equipped with an USB interface. The record is delivered as PDF or CSV format, both are manageable with common and free PC software applications. An intuitive operation menu guides you through the complete jointing process. For fusion data input a barcode reader pen or a scanner is connected. The entire welding process is controlled and regulated with energy output compensation depending on ambient temperature and the indication of cooling time. Robust aluminum housing with convenient cable winding and handle for weight balanced transport. The unit is suitable for jointing in series.

Scope of delivery: dedicated transport case, pouch for optical pen or scanner, 2 pairs of angle adapter clips 4,0 mm and 4,7 mm, operation instructions and configuration chart.

Technical Data

Ambient temperature	-10°C to +45°C
Mains voltage	180 V - 265 V AC
Mains frequency	40 Hz - 70 Hz
Fusion voltage	8 - 48 V AC
Fusion current	max. 90 A
Suggested power generator	3,5 kVA (5,0 kVA for fittings with Ø>200mm)
Protection	Class 1 / IP 54
Mains cable	4 m
Fusion cable	4 m
Interface	USB (type A) for PC communication and software updates
Dimensions (WxHxD)	280 x 480 x 320 mm
Weight incl. cables	ca. 21,7 kg
Display	LCD (20 alphanumerical char. x 4 lines), contrast adjustment, blue background, white characters
Languages	10

description	Code	kg
Barcode reader pen, transport case	790 160 004	30.000
Barcode scanner, transport case	790 160 005	30.000
Barcode reader pen, transport case, Russian language	790 160 020	30.000
Barcode scanner, transport case, Russian language	790 160 021	30.000

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
Phone +41 -(0)52-631 1111
e-mail: info.ps@georgfischer.com
Internet: <http://www.piping.georgfischer.com>